



UGR1124 | UPR1124

DECKOVER FLATBED TRAILERS



Trailer details may differ from image

INDUSTRY BEST WARRANTY

2 YEAR WARRANTY

Unmatched Two-Year Bumper-to-Bumper Warranty on all components. Five-Year Structural Warranty. Ask us for details.

Road Warrior.

The Brandt Work Ready™ Deckover Flatbed Trailers delivers superior capacity to get your your agricultural and landscape equipment where it's going, every single day. This rugged model works as hard as you do, while taking all the punishment you can dish out.

① Built to Last

Brandt trailers are purpose-built to maximize your productivity from dusk till dawn, until the job gets done:

- A Work Ready™ frame built to reduce frame deflection under load, enhancing vehicle stability.
- The ramps are built to handle full equipment weight, enabling you to optimize your trailer for the task at hand.
- Reliable design and long-lasting components reduce total cost of ownership.

② Easier to Operate

These trailers are designed for fast, effortless loading so you can start working sooner:

- Bolt-on key components are easily replaceable for fast maintenance, making this a fully serviceable design for maximum uptime.
- Trailers accommodate any kind of equipment without hassle, ensuring superior versatility.
- 10,000 lb jacks are included as standard equipment to make coupling and uncoupling trailer effortless.

③ Safer

Safety is critical, so these models are designed with key features to maximize operator protection:

- Optional undercarriage toolbox, lower side step, and hydraulic ramps allow operators to work safely.
- Dependable axles ensure positive hitch weight distribution and overall stability when hauling concentrated heavy payloads.
- Pressure treated spruce/pine decking provides a harder, longer lasting surface, capable of standing up to more abuse.

Powerful Value. Delivered.

DECKOVER FLATBED TRAILERS TECHNICAL SPECIFICATIONS

QUICK REFERENCE CHART	UGR1124 Deckover Flatbed		UPR1124 Deckover Flatbed
	TRIDEM	TANDEM	TANDEM
Base Unit Key Specifications			
RELIABILITY - RATED CAPACITY			
GVWR (lb)	22,000	25,000	23,000
Rated Payload (lb)	15,600	18,400	17,000
Suspension	Equalized Leaf Spring		
Axle Rating (lb)	3 x 7000	2 x 10,000	2 x 10,000
DURABILITY - STRUCTURE			
HSS Mainframe Size (in)	12" I-Beam		
Pressure-Treated Spruce/Pine Decking	●	●	●
Polyurethane Primer & Paint	●		
DIMENSIONS			
Total Length (ft)	38.4		35.1
Fixed Deck Length (ft)	24		24
Tail Length (ft)	5		5
Deck Width (in) – inside fender to fender	102		102
Deck Height (in)	35.5		35.4
INCLUDED EQUIPMENT			
Hitch Type	Gooseneck		Bumper
Jackleg Speeds	Single	Single	Single
Jackleg Lift Capacity (lb)	2 x 10,000		2 x 10,000
Tire Size	ST235/80R16 LRE		ST235/80R16 LRE
Premium Radial Tires - speed rated to 120 kph	10 ply		10 ply
Heavy Duty Toolbox	●		●
EASY TO OPERATE - SAFETY & CONVENIENCE FEATURES			
Spring Assist Beavertail Ramp - 24" x 60"	●	●	●
Premium Protected Wiring	●		
Breakaway Switch – includes LED test lights, battery & charger	●		
Integral Footholds	●		
Tier 1 LED Lighting System	●		
Forward Self-Adjusting Brakes	●		
EZ-Lube Oil Bath Axle Bearings		●	●
EZ-Lube Grease Axle Bearings	●		
Black (Silver for Dual) Steel Wheels	●		
Chain Rack/Tray	●		
Spare Tire & Carrier	○		

AVAILABLE ACCESSORIES: Locks for hitches

● Included at no extra cost ○ Option available